



## Network

## MPEG-4



Software Screenshot

Compression	MPEG-4 on CIF Mode, M-JPEG on Frame Mode
Display Speed	Real Time 120 Images Per Second
Adjustable Recording Speed	Frame Mode: 30, 15, 7, 3 Images Per Second CIF Mode: 120, 60, 30, 15 Images Per Second
Display Resolution	720 x 480
Recording Resolution	Frame Mode: 720 x 480 with 30 IPS CIF Mode: 352 x 240 with 120 IPS
Video Inputs	4 Channel 1Vp-p 75Ω BNC with Looping
Video Outputs	1-Main Monitor Output BNC and 1-Call Monitor Output BNC
Recording Mode	Manual, Timer, Motion, Alarm, Remote
Alarm Input	4 Inputs
Alarm Output	1 Output
Audio	1 Input / 1 Output (Mono)
Motion Detection	16 x 12 Grids Per Camera / 4 Adjustable Variables for Precise Detection
PTZ Support	RS-485 Output
Notification	Email and Upload Images to FTP Site's Specific Account
Storage	1 HDD Slot up to 500GB
Dwell Time	Programmable with Adjustable Dwell Time
Zoom	2X Digital Zoom (live mode)
Video Adjustable	Hue, Color, Contrast, Brightness
Back-up	Network Remote Back-Up
Network	TCP/IP, PPPoE, DHCP, and DDNS Function
Operation Temperature	50°F~104°F (10°C~40°C)
Power	19VDC / 42 Watts
Dimensions	343(W) x 223(D) x 59(H) mm