



## Network

## MPEG-4



Software Screenshot



New Version Now  
Includes Remote Control

Compression	MPEG4 on CIF Mode, M-JPEG on Frame Mode
Display Speed	Real Time 120 Images Per Second
Adjustable Recording Speed	Frame Mode: 30, 15, 7, 3 Images Per Second CIF Mode: 120, 60, 30, 15 Images Per Second
Display Resolution	720 x 480 (D1)
Recording Resolution	Frame Mode: 720 x 480 with 30 IPS CIF Mode: 352 x 240 with 120 IPS
Video Inputs	4 CH 1Vp-p 75Ω BNC with Looping
Video Output	1-Main Monitor Output BNC and 1-Call Monitor Output BNC
Recording Mode	Manual, Timer, Motion, Alarm, Remote
Alarm Input / Output	4 Inputs / 1 Output
Audio	1 audio input / 1 audio output (Mono)
Motion Detection	16 x 12 grids per camera / 4 Adjustable Variables for Precise Detection
PTZ Controls	RS485 Output on Board
Notification	E-mail and Upload Images to FTP Sites Specific Account
Search Mode	Time/Date, Calendar, Event
Storage	1 HDD Slot up to 500GB
Dwell Time	Programmable weith Adjustable Dwell Time
Zoom	2 x Digital (live Mode)
<b>Video Adjustable</b>	<b>Hue, Color, Contrast, Brightness</b>
IR Remote	Included
Back-up	Network Remote Back-Up / USB Port for Easy Back-Up
Network	TCP/IP, PPPoE, DCHP and DDNS Function
Operation Temperature	50°F~104°F (10°C~40°C)
Power	19 VDC / 42W Consumption
Dimensions	343mm (W) x 223mm (D) x 59mm (H)